



WATER BARRIER/SHEATHING RENAILING AFFIDAVIT

Rev: 4 | Revision Date: 10/24/2024 | I.D. Number: WBSRA

WATER BARRIER/SHEATHING RENAILING AFFIDAVIT

THIS FORM IS NOT TO BE SUBMITTED WITH THE PERMIT APPLICATION.
IT MUST BE PROVIDED AT THE JOB SITE BEFORE THE TIN-CAP INSPECTION.

PERMIT NUMBER _____

OWNER _____

JOB ADDRESS _____

I HERBY CERTIFY THAT:

- A. THE DECK HAS BEEN RE-NAILED AT 6" ON CENTER FOR PLYWOOD DECKS AND 2 FASTENERS PER BOARD FOR BOARD ON BOARD DECKS WITH 8D RING SHANK NAILS WITH THE FOLLOWING MINIMUM DIMENSIONS:

0.113 INCH NOMINAL SHANK DIAMETER	RING DIAMETER OF 0.012 OVER THE SHANK DIAMETER	16 TO 20 SHANKS PER INCH
0.280 INCH FULL ROUND HEAD DIAMETER	RING SHANK TO EXTEND A MINIMUM OF 1 1/2" FROM THE TIP OF THE NAIL	2 1/2 INCH NAIL LENGTH.

- B. SECONDARY WATER BARRIER HAS BEEN HAS BEEN INSTALLED IN ACCORDANCE WITH FBC 1518.2.1:

_____ ENTIRE DECK COVERED WITH SELF-ADHERING MODIFIED BITUMEN COMPLIANT WITH ASTM D1970

_____ 4" STRIP OF SELF-ADHERING COMPLIANT WITH TABLE 1518.2.1 OF 2023 8TH EDITION OF THE FBC HAS BEEN APPLIED TO ALL JOINTS IN THE PLYWOOD DECK.

_____ 2 - LAYERS OF ONE OF THE FOLLOWING: ASTM D226 TYPE II, OR D4869 TYPE III, OR IV OR D8257 UNDERLAYMENT HAS BEEN INSTALLED PER FBC HVHZ.

EXCEPTIONS

- 1) ROOF SLOPES < 2:12 HAVING A CONTINUOUS ROOF SYSTEM SHALL BE DEEMED TO COMPLY WITH REQUIREMENTS FOR A SECONDARY WATER BARRIER.
- 2) CLAY AND CONCRETE TILE ROOF SYSTEMS INSTALLED AS REQUIRED BY THE FLORIDA BUILDING CODE ARE DEEMED TO COMPLY WITH THE REQUIREMENTS FOR SECONDARY WATER BARRIERS.

- C. A COPY OF THIS AFFIDAVIT HAS BEEN DELIVERED TO THE HOMEOWNER.

QUALIFIER'S SIGNATURE _____ DATE _____
(LICENSED ROOFING CONTRACTOR)

NAME PRINTED _____ LICENSE NUMBER _____

NOTARY _____ DATE _____

SEAL:

FOR STAFF USE ONLY:

INSPECTOR'S NAME COLLECTING THE DOCUMENT:

DATE: _____

PERMIT NUMBER: _____